

COLE-TUVE, INC.

BOX 233, WHITE MARSH, MD 21162-0233
 PHONE: (410) 933-0700
 FAX: (410) 933-0600



Siemens Industry, Inc.
 21 North Main Street
 Milan, Ohio 44846

Att: Kirk Rounds

E-Mail - kirk.rounds@siemens.com
 T -419-499-4616 Cell - 440-897-6804

ANGLE ROLLS | PLATE ROLLS
 SHEET METAL ROLLS
 PRESS BRAKES | C-FRAME PRESSES
 TRIMMING & BEADING MACHINES
 HORIZONTAL METAL-CUTTING BANDSAWS
 OPEN-BACK & STRAIGHT SIDE PRESSES
 HIGH SPEED CIRCLE CUTTING MACHINES
 4-COLUMN HYDRAULIC PRESSES
 HYDRAULIC BOX & PAN/LEAF BRAKES

REFERENCE: Your Call

QUOTATION 7081, Page 1

(X) BY E-MAIL () BY FAX (X) BY MAIL

DATE: February 11, 2013

WE ARE PLEASED TO SUBMIT FOR YOUR CONSIDERATION:

1- New COLE-TUVE By Sahinler Angle and Shape Bending Roll, Model ARS-4.
 Hydraulic. Double-Pinch Type.

Features:

- Heavily proportioned welded steel frame for rigidity and stability.
- All three rolls are driven.
- Infinitely variable rolling speeds.
- Hydraulic adjustment of the lower rolls for double prebending capability.
- Shafts are hardened and ground and rotate on amply-sized bearings.
- Standard rolls are hardened and handle many shapes.
- Operates in horizontal or vertical plane.
- 2 - Electronic digital readouts (LED) for the positions of the adjustable rolls, with programmable roll position pre-set and memory.
- 3-axis mechanical guide rolls for angles leg-out and leg-in, manually adjusted.
- Operating controls in a rolling console.

Capacities, mild steel:

- Angle iron, leg-out - 4" x 4" x 1/2"
- Angle iron, leg-in - 4" x 4" x 3/8"
- Flat bar on flat - 6-1/4" x 1-3/8"
- Flat bar on edge - 4" x 3/4"
- "T" iron, leg out 4", "T" Iron, leg in 3-1/2"
- Square bar - 2-3/8"; Round bar - 3" (SP)
- Channel iron, leg-in - 6.3"
- Channel iron, leg-out - 6.3"
- Pipe - 4" Schedule 40 (SP)
- Round tubing - 5" x 12 ga. (SP), Square tubing - 3" x 3" x 3/16"
- Rectangular tubing, hard way - 4" x 1-1/2" x 10 ga.
- Shapes marked (SP) require special rolls. For some of the other shapes, special rolls may improve rolling results.

Specifications:

- Diameter of the rolls - upper and lower - 12-3/8"
- Diameter of the rolls shafts - 3.93"
- Rolls adjustment - powered hydraulic
- Rolling speeds, infinitely variable - 0 to 23 feet per minute
- Motor HP - 10
- Working plane - combination horizontal/vertical
- Dimensions - 58" L x 79" W x 67" H
- Weight - 8800#

continues...

THE "TERMS AND CONDITIONS OF QUOTATION AND SALE" ON THE REVERSE SIDE HEREOF ARE MADE A PART OF THIS QUOTATION AND OF THE CONTRACT FOR ANY RESULTING SALE.		WARRANTY: FOR DETAILS OF THE LIMITED WARRANTY WHICH APPLIES, SEE THE "TERMS AND CONDITIONS OF QUOTATION AND SALE".
F.O.B.	DELIVERY	PAYMENT TERMS

COLE-TUVE, Inc.